

NH-1800SE

Freestanding Cash Dispenser

2nd to None in Retail ATMs

Features

- **Maximum Reliability** - NH-1800SE is designed to provide 2nd to none reliability in the retail market locations with highest uptime and with minimum maintenance needs. You won't have to worry about replacing the parts or sudden breakdowns because the NH-1800SE is designed to run for a very long time, problem-free.
- **Environment Stewardship** - With quality comes also responsibility. NH-1800SE is equipped with energy saving features like low energy LCD and long lasting ATM parts with minimum implications to the environment.
- **Flexibility** - NH-1800SE is designed with open architecture platform allowing for easy future upgrades and module modifications. Modular design is one of ways in which we are trying to save our customers' cost and provide maximum convenience.
- **Ultimate Functionality** - NH-1800SE offers ultimate functionality featuring bill payment, funds transfer, mobile top-up in a highly user friendly interface for maximum convenience and very easy transition.
- **Maximum Protection** - Complying to standards in various regions worldwide, Nautilus Hyosung offers advanced security measures while highly secured integrity of the NH-1800SE prevents any attempted security breaches from occurring. NH-1800SE can also be easily integrated with monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



Driving tomorrow's technology
NAUTILUS HYOSUNG

Dependable Customer Service:

We understand the importance of speedy resolution to any issues arising in the operation. Our representatives offer real solutions with real results for maximum return on your investment.



NH-1800SE



System Control

- Windows CE Platform
- Microsoft® Window® CE

Communication

- TCP/IP (SSL configurable)
- Dial-up (optional pre-dial function)

Customer Display

- 8" color TFT LCD

Input Type

- 4 x 2 function keys
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Supports Three Languages

- English
- Spanish
- French

Supports Quick

Pick Lotto Software



Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- 1,000-note removable cassette

Optional

- 2,000-note removable cassette can be upgraded to 2 cassettes for 4,000 notes

Printer

- 80 mm graphical thermal receipt printer

Security

- UL® Business Hour safe
- Mechanical combination lock
- **Optional** UL® Level 1 safe
- **Optional** electronic safe lock
- **Optional** KABA Mas Cencon safe lock

Power Supply

- AC 110 ~ 230V, 50 ~ 60 Hz

Operating Environment

- Temperature : 32°F ~ 104°F
- Humidity : 20% ~ 85%

Dimension and Weight

- Height : 1,304 mm (51.3")
- With topper : 1,675 mm (65.3")
- Width : 400mm (15.7")
- Depth : 580mm (22.8")
- Weight : 120kg (265 lbs)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.



Cheongdam Bldg., 52 Cheongdam-Dong, Gangnam-Gu, Seoul, Korea 135-764
TEL : +82-2-510-0441 FAX : +82-2-3442-7993
<http://www.nautilus.hyosung.com>